

■ スパイラルダクト直管寸法表

呼径		管厚		各部寸法			参考重量
D	t	W	P	D ₁	kg/m		
75	0.5	6	60	79.0	1.2		
100	0.5	6	87	104.0	1.6		
	0.6	7	//	104.8	1.9		
	0.8	8	//	106.4	2.5		
125	0.5	6	86	129.0	2.0		
	0.6	7	//	129.8	2.4		
	0.8	8	//	131.4	3.1		
150	0.5	6	140	154.0	2.2		
	0.6	7	140	154.8	2.7		
	0.8	8	131	156.4	3.7		
	1.0	10	130	158.0	4.6		
175	0.5	6	138	179.0	2.6		
	0.6	7	138	179.8	3.1		
	0.8	8	129	181.4	4.3		
	1.0	10	128	183.0	5.3		
200	0.5	6	137	204.0	2.9		
	0.6	7	137	204.8	3.5		
	0.8	8	129	206.4	4.9		
	1.0	10	128	208.0	6.1		
225	0.5	6	136	229.0	3.3		
	0.6	7	136	229.8	4.0		
	0.8	8	128	231.4	5.5		
	1.0	10	127	233.0	6.8		
250	0.5	6	136	254.0	3.7		
	0.6	7	136	254.8	4.4		
	0.8	8	128	256.4	6.1		
	1.0	10	127	258.0	7.6		
275	0.5	6	136	279.0	4.0		
	0.6	7	136	279.8	4.9		
	0.8	8	127	281.4	6.7		
	1.0	10	126	283.0	8.4		
300	0.5	6	135	304.0	4.4		
	0.6	7	135	304.8	5.3		
	0.8	8	127	306.4	7.4		
	1.0	10	126	308.0	9.1		
325	0.6	7	135	329.8	5.7		
	0.8	8	127	331.4	8.0		
	1.0	10	126	333.0	9.9		
350	0.6	7	135	354.8	6.2		
	0.8	8	127	356.4	8.6		
	1.0	10	126	358.0	10.7		
375	0.6	7	135	379.8	6.6		
	0.8	8	127	381.4	9.2		
	1.0	10	126	383.0	11.4		
400	0.6	7	135	404.0	7.1		
	0.8	8	127	406.4	9.8		
	1.0	10	126	408.0	12.2		
450	0.6	7	135	454.8	8.0		
	0.8	8	127	456.4	11.1		
	1.0	10	125	458.0	13.7		
500	0.6	7	134	504.8	8.8		
	0.8	8	126	506.4	12.3		
	1.0	10	125	508.0	15.2		
550	0.6	7	134	554.8	9.7		
	0.8	8	126	556.4	13.5		
	1.0	10	125	558.0	16.7		
600	0.6	7	134	604.8	10.6		
	0.8	8	126	606.4	14.7		
	1.0	10	125	608.0	18.2		
650	0.8	8	126	656.4	15.9		
	1.0	10	125	658.0	19.7		
700	0.8	8	126	706.4	17.2		
	1.0	10	125	708.0	21.3		
750	0.8	8	126	756.4	18.4		
	1.0	10	125	758.0	22.8		
800	0.8	8	126	806.4	19.6		
	1.0	10	125	808.0	24.3		
850	1.0	10	125	858.0	25.8		
900	1.0	10	125	908.0	27.3		
950	1.0	10	125	958.0	28.8		
1000	1.0	10	125	1008.0	30.3		

(注) 出荷工場により一部の製品は、寸法および仕様が異なる場合があります。詳しくはお問い合わせ下さい。〔定尺は4mです〕